



> PRINT > COPY > SCAN > FAX

TASKalfa 6053ci

COLOUR MULTIFUNCTIONAL
FOR A4/A3 (SRA3) FORMAT

HIGH-LEVEL SECURITY AS PRIORITY



Possessing all of the latest developments in technology to provide maximum security for your data, the new TASKalfa 6053ci ensures that information is kept under virtual lock and key. The deployment of innovative security features ensure that information which passes through this multifunctional product is not put at risk. Beyond protecting information, the device also offers high quality printing with vibrant colour, which can be finished with a range of flexible options, ideal for a variety of document types, lengths and formats. An award-winning engine also offers unbeatable reliability and consistency to make the product truly unique in providing a solution to the needs of a business in any industry and of any size.

- > Up to 60/55 pages per minute A4 in b/w and colour
- > Outstanding image quality due to advanced colour technology
- > User friendly and intuitive 10.1 inch operation panel
- > Advanced paper handling from A6 up to SRA3 for up to 7,150 sheets
- > Great range of high speed colour scanners and productive finishing options
- > High-level build in security features including data encryption, Trusted Platform Module, Secure Boot and Run Time Integrity Check
- > Long-life components providing exceptional efficiency and reliability, and less waste
- > Optional Fiery Controller for highest productivity and colour quality

GENERAL

Technology: KYOCERA TASKalfa Laser Colour, HyPAS solution platform
Touch panel size: 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15°-90° swivel mounted
Engine speed (pages per minute): Up to 55/27 ppm A4/A3 in colour, up to 60/30 ppm A4/A3 in b/w; Duplex print speed: 60 ppm A4; Duplex copy speed: 60 ppm, A4
Resolution: 4800dpi equivalent x 1200dpi (print), 600 x 600 dpi (scan/copy)
Warm-up time from power on: Approx. 17 seconds or less
Time to firstprint: 3.8 / 5.1 seconds or less in b/w / colour
Time to firstcopy: 4.1 / 6.2 seconds or less in b/w / colour (DP); 3.4 / 4.4 seconds or less in b/w / colour (Platen)
CPU: QorlQ T1024 (Dual Core) 1.2GHz
Memory (standard max.): 4 GB RAM + 8 GB SSD + 320 GB HDD
Standard interface: Standard interface: USB 3.0 (Super-Speed USB), 4 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), optional Wi-Fi (IEEE 802.11b/g/n), 2 eKUIO slots, for optional internal print server or for optional fax system, slot for optional Wireless LAN, Slot for optional SD Card, NFC tag
Dimensions (W x D x H): Main unit: 602 x 665 x 790 mm
Weight: Main unit: Approx. 95 kg
Power source: AC 220 V ~ 240 V, 50/60 Hz
Power consumption:
 Printing: 851 W
 Copying: 851 W
 Ready mode: 60 W
 Low power mode: 50 W
 Sleep mode: 0.7 W
Noise (sound pressure level ISO 7779 measurement distance of 1 meter):
 Copying/Printing: 54.6 dB (A) in colour
 Stand-by: 35 dB (A)
Safety standards: GS, TÜV, CE.
 This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.
Input capacity:
 Multipurpose tray: 150 sheets, 52 – 300 g/m² (Banner 136 – 163 g/m²), A6R – SRA3 (320 x 450 mm), Custom (98 x 148 to 297 x 457.2 mm), Banner max. 304.8 x 1,220 mm; Standard universal paper cassette: 2 x 500 sheets, 52 – 300 g/m², Upper cassette A6R up to A4R, lower cassette A6R up to SRA3, Max. input capacity with options: 7,150 sheets A4 Duplex unit: Duplex as standard supports A6R – SRA3, 64 – 256 g/m²
Output capacity: Standard 500 sheets face-down, max. output capacity 4,300 sheets

PRINT FUNCTIONS

Controller language: PRESCRIBE
Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS
Operating systems: All current Windows operating systems, Mac OS X Version 10.9 or higher, UNIX LINUX, as well as other operating systems on request
Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL 3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)
Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage functionality
 Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google cloud print

COPY FUNCTIONS

Max. original size: A3 / Ledger
Continuous copying: 1 – 9999
Zoom range: 25 – 400% in 1% steps
Preset magnification ratios: 5R/5E,
Exposure mode: Auto, manual: 16 steps
Image adjustments: Text + photo, text, photo, Diagram/map
Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, skip blank page, ID copy

SCAN FUNCTIONS

Functionality: Scan to e-mail, Scan to FTP, Scan to SMB, Scan to USB Host, Scan to box, Network TWAIN, WIA/WSD scan
Scan speed: 220 images per minute (300 dpi, A4 duplex, with DP-7130) in b/w and colour
Scan resolution: 600dpi x 600dpi, 400dpi x 400dpi, 200dpi x 400dpi, 300dpi x 300dpi, 200dpi x 200dpi, 200dpi x 100dpi; 256 greyscale per colour
Max. scan size: A3, Ledger
Original recognition: Text, photo, text + photo, Light Text / Fine Line, optimised for OCR
File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, Searchable PDF(option), MS Office file(option)

FAX FUNCTIONS (OPTIONAL)

Compatibility: IITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: Max. 3 seconds (JBIG)
Scanning speed: 2.0 seconds or less
Maximum original size: A3, Banner up to 1,600 mm
Compression method: JBIG, MMR, MR, MH
Features: Network faxing, rotate transmission, rotate reception, encrypted transmission and reception, duplex fax reception, memory reception, mailbox, remote diagnostics, polling transmission and reception, broadcast, Optional Internet-fax, dual fax with second fax system 12


CONSUMABLES

Average continuous toner yield in accordance with 5% coverage A4.
TK-8515K Toner-Kit: Toner black for 30,000 pages A4
TK-8515C, TK-8515M, TK-8515Y Toner-Kits: Toner cyan, magenta, yellow for 20,000 pages
WT-8500 Waste Toner Bottle: 40,000 sheets (in accordance with 5% coverage b/w: colour = 7 : 3)
Staple cartridge:
SH-10 5000 x 3 staples, for DF-7100, DF-7120, BF-730 and BF-9100
SH-12 5000 x 3 staples, for DF-7110
SH-14 5000 x 5 staples, for DF-7130

OPTIONS

Fax System 12
Internet Fax Kit (A)
Scan Extension Kit (A):
 Scan to searchable PDF solution (embedded OCR), convert to PDF or MS Office (docx, xlsx, pptx)
Printing System 15: Fiery Controller
Printing System Interface Kit 15: Interface board for Fiery
Paper handling
DP-7100 Document processor: (Reversing), 140 sheets, 35 - 160 g/m² (simplex), 50 - 120 g/m² (duplex), A6R-A3, Banner up to 1,900 mm

DP-7110 Document processor: (one-path duplex scanning) 270 sheets at 50 - 80 g/m², 35 - 220 g/m² (simplex), 50 - 220 g/m² (duplex), A6R - A3, Banner up to 1,900 mm
DP-7130 Document processor: (one-path duplex scanning with ultrasonic sensor), 270 sheets at 50 - 80 g/m², 35 - 220 g/m² (simplex), 50 - 220 g/m² (duplex), A6R-A3, Banner up to 1,900 mm
DT-730(B) Document tray
PF-7100 Paper feeder: 2x 500 sheets, 52 – 300 g/m², A6R – SRA3
PF-7110 Paper feeder: 2x 1,500 sheets, 52 – 300 g/m², A4, B5, letter
PF-7120 A4 side Deck: 3,000 sheets, 60 – 300 g/m², A4, B5
DF-7100 Inner finisher: 500 sheets A4, 52–300 g/m², A6R–SRA3
DF-7110* Document finisher+AK-7110:
 Main tray: 4,000 sheets A4;
 Sub tray: 200 sheets A4; 52 – 300 g/m²; A6R – SRA3
 Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions
DF-7120* Document finisher+AK-7110:
 1,000 sheets A4, 52 – 300 g/m², A6R – SRA3,
 Stapling up to 50 sheets A4 or 30 sheets A3 at 3 position
DF-7130* Document finisher+AK-7110: Main tray: 4,000 sheets A4; Sub tray: 200 sheets 52–300 g/m² A6R–SRA3;
 Stapling up to 100 sheets A4 or 50 sheets A3 at 3 positions
AK-7110 Attachment kit for DF-7110, DF-7120 and DF-7130, 100 sheets, 52–300 g/m², A6R–SRA3, * Bridge unit AK-7110 is required when using a finisher
PH-7C/PH-7D Punch unit for DF-7110/DF-7120/ DF-7130: 2-hole/4-hole/Swedish type, 60 – 256 g/m², A5R – A3
MT-730(B) Mailbox sorter for DF-7110: 7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 163 g/m²
BF-730 Booklet and tri-folding unit for DF-7110
 Half-folding: 52–256 g/m², A3, B4, A4R
 Booklet: Max. 16 sheets (64 pages, 60–90 g/m²)
 Non-staple folding: Max. 5 sheets (60–90 g/m²)
 Tri-folding: Max. 5 sheets (60–105 g/m², A4R)
 Multi tri-folding: 5 sheets (60–90 g/m²), 3 sheets (91–105 g/m²)
BF-9100 Booklet and tri-folding unit for DF-7130
 Half-folding: 52–256 g/m², A3, B4, A4R
 Booklet : Max 20 sheets (80 pages, 60-90g/m²) or Max 13 sheets (52 pages 91-105g/m²)
 Non-staple : Max 5 sheets(60-90g/m²) or Max 3 sheets(91-105g/m²)
 Tri-folding : Max 5 sheets(60-90g/m²) or Max 3 sheets(91-105g/m²)
JS-7100 Job separator:
 100-sheet internal job separator, 52 – 300 g/m², A5R – SRA 3
3PH-7120: Inner punch unit for DF-7100 inner finisher
PH-7130: Inner punch unit for DF-7100 inner finisher/ Swedish type
Banner Guide 10: Banner paper feeding guide, 10 sheets
Keyboard holder 10
NK-7120 Numeric keypad
USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available. The card holder is standard
UG-33 AC: ThinPrint support
UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850/ Diablo 630)
Optional interface
IB-35: Direct Wi-Fi Interface
IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/ 1,000 BaseT
IB-51: Wireless LAN Interface (802.11b/g/n)
Platen cover (E)
CB-7100W: Wooden cabinet
CB-7110M: Metal cabinet



KYOCERA Document Solutions Europe B.V. – Bloemlaan 4 –
 2132NP Hoofddorp – The Netherlands
 Tel +31 (0)20 6540 000 – Fax +31(0)20 653 1256
www.kyoceradocumentsolutions.eu – info@deu.kyocera.com

KYOCERA Document Solutions Inc. – 2-28, 1-Chome – Tamatsukuri
 Chuo-Ku – Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.